

## TECH SPECS

### ENEVO WASTE SENSOR FOR LIQUID MATERIALS IN TANKS

#### OVERVIEW

The WE-009TL tank level sensor has been designed and built to accurately measure tank fill levels in **harsh environmental conditions**. It uses **robust ultrasonic sonar technology** together with **temperature and motion sensors** and **smart software** to not only measure the fill level, but also automatically detect important events, such as container collections, deliveries, fire and vandalism. **Advanced algorithms** are applied to determine the fill level even if the surface of the contents is unevenly shaped, which is often the case. Measurements are performed at configurable intervals, usually once per hour. Measurements are automatically communicated to the Enevo server using 4G low power cellular networks (LTE Cat-M1).

#### FEATURES

- Continuously monitors fill level
- Automatically detects collections and deliveries
- Easily retrofitted or pre-installed to almost any tank with a bung fitting
- 1.5" and 2.5" bung fitting adapters available
- Minimal maintenance
- Wireless communications and alarming
- Enhanced fixing structure designed for durability Totally independent with internal power supply lasting for 10+ years\*
- Easy remote configuration and software updates

\* Estimated battery life time using recommended settings in optimal circumstances. Actual battery life may vary depending on how frequently the sensor communicates with the network and various measurement circumstances such as configuration, wireless signal strength and temperature.



#### WE-009TL SENSOR

<b>Dimensions and Weight</b>	<b>Measurement</b>
Dimensions: 170 mm (H) x 118 mm (W) Weight: 1.3 lbs (~590g)	Range: 160 inches (~400 cm) Accuracy: Typically ± 1 inch (2.54 cm)
<b>Environmental</b>	<b>Power</b>
Ratings: IP 69, IK 10 Temp. range: -40 to +185 °F (-40 to +85°C)	Type: 3.6V Lithium battery Battery life: 10+ years *
<b>Wireless Connectivity</b>	<b>Physical Characteristics</b>
LTE Cat-M1 (4G), GSM-fallback (2G): 700 / 1700 / 1900 MHz	Body: Proprietary polyurethane resin and glass fiber re-inforced polypropylene 1.5" and 2.5" NPT fitting

info@enevo.com  
+1 (844) 363 8687  
www.enevo.com



© 2022 Enevo, Inc.

The information provided in this brochure contains merely general descriptions of characteristics of performance which in case of actual use do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract.

# enevo